

Product Name :
Bitumen Bending Rheometer

Product Code :
NLAB-EDUCATIONTVET11008



Description :

Bitumen Bending Rheometer

Technical Specification :

The flexural rheometer for bitumen makes it possible to measure the flexural performance at low temperature of a bituminous binder.

These tests consist in applying a force on a sample immersed in a temperature-controlled bath in order to determine different rate of deformation depending on the temperature.

The system consists of a regulated low temperature bath, an easily removable bending unit to allow the installation of the sample, an external cold unit with temperature control and a calibration kit in its case.

The unit has a stainless steel frame and an integrated loading rod with a rounded loading tip.

The device includes molds conforming to ASTM / AASHTO standards as well as a complete calibration kit in its case.

Characteristics :

- Load: 0 to 200 g.
- Accuracy per test cycle: $\pm 0.5g$.

- Duration of cycles: defined by the operator.
- Load cell capacity: 500 g.
- Sample holder: 25 mm diameter spaced 101.6 mm apart.
- Operating temperature: ambient at -40 ° C.

Silent compressor

IDG3 membrane dryer

Filtered

Connection kit

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003