Phone: +91-9896600003

Email: sales@naugralabequipments.com

Product Name:

DSB and SSB-SC Amplitude Modulation and Demodulation Trainer

Product Code:

NLAB-EDUSCHOOLEQ198001



Description:

DSB and SSB-SC Amplitude Modulation and Demodulation Trainer

Technical Specification:

Trainer has been designed with a view to provide practical and experimental knowledge of Amplitude Modulation / Demodulation technique as practically implemented in Analog Communication system on a SINGLE P.C.B. of size 300 x 400mm.

Object:

To Study of

Amplitude Modulation & Demodulation:

Generate AM signal by modulation with audio signal generator

Measure modulation index of A.M. signal

Demodulate AM signal using diode detector(envelope detector)

Generate voice signal AM modulation and demodulation using Mic.

Observe the effect of DC signal input on AM output

Phone: +91-9896600003

Email: sales@naugralabequipments.com

Demodulate AM signal by square law detection
DSB-SC Amplitude Modulation & Demodulation:
Generate DSB-SC AM signal
Demodulate DSB-SC signal using product detector
SSB-SC Amplitude Modulation & Demodulation:
Generate SSB-SC AM signal
Demodulate SSB-SC signal using product detector
Feature:
The board consists of the following built-in parts:
IC Regulated Power Supply:
± 15 DC and +5V DC at 100mA.
AF Modulation signal generator:
Sine wave
Frequency Range:
300 Hz to 3.4 KHz
Amplitude:
0 to 5 Vpp.
RF carrier signal oscillator.
Frequency Range:
100 KHz to 1 MHz.
Amplitude:
0 to 10 Vpp.
Local Oscillator:
400 KHz to 500 KHz.
Band Pass Filter:
452 KHz to 458 KHz.
DC Source Variable power supply to see the effect of DC on the output waveform:

Phone: +91-9896600003

Email: sales@naugralabequipments.com

-5 to + 5 VDC

Output Audio amplifier with Volume Control.

Input Audio amplifier for modulating external signal from Mike or Tape recorder.

Double Balanced Amplitude modulator

Diode detector.

Product detector

Low pass filter.

Power supply requirement 230V AC, 50 Hz.

Mains ON/OFF switch, fuse and jewel light.

Dynamic Microphone with 4mm Jack Pin.

Loud Speaker with baffle fitted in a box with two metre wire and 2mm Banana pins for connections.

Good Quality, reliable terminal/sockets are provided at appropriate places on panel for connections/ observation of waveforms.

Strongly supported by detailed Operating Instructions, giving details of Object, Theory, Design Procedures, Report Suggestions and Book References

Naugralabequipments

Website: www.naugralabequipments.com, Email: sales@naugralabequipments.com
Address: 6148/6, Guru Nanak Marg,Ambala Cantt,Haryana,India. Phone: +91-9896600003