

Product Name :
Hot Air Sterilizer

Product Code :
NLAB-SCIENTIFICEQ39008



Description :

Hot Air Sterilizer

Technical Specification :

APPLICATIONS OF HOT AIR STERILIZER

Hot/Dry Air Sterilizer is an equipment in which dry heat sterilization process takes place, in which as the name suggests sterilization takes place through hot and dry air.

Dry Heat Sterilization is the most widely used technique in the Pharmaceutical Industry and Biotechnology research labs which is employed to sterilize products that are moisture sensitive and medicinal in nature that can have adverse and inimical effect when steam is used on them.

Dry heat sterilization or de-pyrogenation is a process, which is used to reduce pyrogen level (a pyrogen is a substance which causes fever) with the use of hot air in temperature ranges from 160°C to 300°C.

Dry powder drugs, oil, waxes, soft hard paraffin silicone, injections, implants, ointment, sharp objects, metal parts etc. are some of examples that require dry heat sterilization or De-pyrogenation. The industry includes- Pharmaceutical (drug manufacturing), Biotechnology research labs, Food & Beverage Industries, Dairy plants, Agriculture & Industrial research, Textile industry etc.

Some of the tests and processes which can be performed using Hot/Dry air Sterilizers are- Moisture determination, Out gassing solids, Aging test, Plating, Chemical resistance studies, drying of Paper, rubber, textile, leather etc., Vacuum storage, Electronic process control.

SALIENT FEATURES & CONSTRUCTION OF HOT AIR STERILIZER

Outer Chamber made of M.S. Powder Coated

Inner chamber is made of STAINLESS STEEL (304 grade).

Between the outer and inner body wool is stuffed for insulation and for the prevention of thermal loss

Door Gasket is provided for proper sealing along with heavy hinges and door closing device

At the front transparent see-through window is provided. The glass of the window is unbreakable

2 air controlling valves are provided for the creation of vacuum

Heating elements are made up of high quality Nichrome

Kanthal wire are embedded around the chamber

Supplied with 1 (or) 2 removable shelves

Temperature is controlled by Electronic Digital temperature indicator and is fitted in front for easy visibility

Temperature is displayed on digital LED

Front panel beside the temperature display also includes the ON/OFF switch

Supplied with chord and Plug

Operating Voltage: 22 Volts AV (50 Hz)

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003