

**Product Name :**  
Nauga Lab Electro Pneumatic Trainer

**Product Code :**  
NLAB-EDUCNCLAB110031



**Description :**

Nauga Lab Electro Pneumatic Trainer

**Technical Specification :**

The Electro Pneumatic Trainer outlines basic of pneumatic control systems along with its components and their applications.

It demonstrates the design, construction, and applications of Electro-Pneumatic components and circuits.

**Specification:-**

Single Acting Cylinder:- Bore: 25 mm x Stroke: 100mm, Mounting: Foot

Double Acting Cylinder:- Bore: 25 mm x Stroke: - 100mm, Mounting: Foot

A.F.R. / F.R.L. Unit:- ¼" Connection, 0-10 Kg/cm<sup>2</sup>

Solenoid Valve:- 2 Nos, 5/2 way, ¼" , 230VAC/24 V & 3/2 way, ¼" , 230 VAC/24 V DC

Flow Control Valve:- ¼" (F), Square Body.

Non-Return Valve:- ¼" connection

Block Manifold:- ¼", 6 ways.

AND Valve- Dual Pressure Valve, ¼" connection.

Shuttle Valve:- OR Valve, ¼" connection.

Sintered Silencer:- ¼" connection.

Male Connector:- ¼" connection.

Indicating Lamp:- 24 VDC Operated.

Proximity Sensors:- Type: Inductive 2 wire, Diameter: 18 mm, Sensing Distance: 5 mm.

Pressure Gauge:- 0-7 Kg/cm<sup>2</sup>, connection ½" BSP, Dial Size: 100 mm

Pneumatic Motor- Unidirectional, Free Speed: 22,000 RPM, Air pressure: 0-90 psi,

Electrical control panel- MS Powder coated panel with switches, indicator, Test Points, controller on front fascia, UK 2.5 Terminal Connectors mounted on DIN rail channel, Use of 1sq mm multistrand wire with proper insulated Lugs, Ferruling & neat wire dressing & clamping Wires & power cables are seated through 1"x1" PVC cable tray.

Dimension: 1ft (L) x 1ft (W) x 1ft (H)

Quick Push-Pull connectors:- Sufficient shall be supplied for branching of the tubing for making of the circuitry.

Plastic Tubing:- PUN 4 x 0.75, Exterior Diameter-6mm, Interior Diameter- 4mm, Transparent – 10mtr, Blue-10mtr

Relay Module- 24V DC supply, 2 NO/NC contacts, panel mounting type.

Air Compressor (Optional):- Tank capacity: 25 Liters, Discharge: 2 CFM

Motor: 2 H.P. 230 V AC Operated, Working pressure: 5-6 kg/cm<sup>2</sup>.

Feature:-

Compact Ergonomic Design.

User-Friendly, Self Explanatory Systems.

Leak-proof Safety Measures, sturdy piping & Robust Construction.

Enhanced Electrical Safety Considerations.

Training Manuals mimic Charts for Operation Ease.

M.S. powder coated cubical plant with standard Instrument Assemblies.

Inbuilt Safety Measures to avoid improper usage.

Relay board logic circuit operation.

Profile Plate

## Naugralabequipments

**Website:** [www.naugralabequipments.com](http://www.naugralabequipments.com), **Email:** [sales@naugralabequipments.com](mailto:sales@naugralabequipments.com)

**Address:** 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003