

Product Name :
Nauga Lab Microprocessor Dissolution Test Apparatus

Product Code :
NLAB-LABORATORYEM58001



Description :

Nauga Lab Microprocessor Dissolution Test Apparatus

Technical Specification :

Microprocessor Dissolution Test Apparatus

Features:-

8 Station

6 Station

Complies with USP, IP specifications

Extremely Useful for Pharmaceutical Labs

Highly Accurate and Easy to Operate

Programmable Stirrer Speed Control i.e. (25 - 200 RPM)

20 x 4 Line Alphanumeric LCD with Backlit

19 Soft Touch Membrane Type Keys

Three Programming Modes i.e. Routine, Sustain and Control

20 Independent Programmable Setups for Routine and Sustain Mode with Storage Facility

200 Samples Storage Facility

Printer Attachment Facility

Audio Visual Indicators for System Status

Easy to Empty & Clean the Water bath with Bottom Drainage

Continuation of Last Sample Run in case of Power Failure

Microprocessor Dissolution Test Apparatus is a solid state instrument designed for the determination of active drug ingredient in any pharmaceutical formulation, tablet or capsule as per IP and USP specifications.

This apparatus evaluates adequate bio-availability and provides necessary information to formulate in the development of therapeutically optimum dosage forms.

The instrument is designed and manufactured for pharmaceutical industries.

It is used in quality control and R & D to determine compliance with the dissolution requirement of the Tablet and Capsule as per USP/IP standards.

Instrument uses the latest microprocessor technology and advanced engineering

techniques so as to give enhanced accuracy and reproducibility.

The system has user friendly prompts, which guide you throughout the measurement process.

System is equipped with 4 line alphanumeric LCD display with backlit and 19 soft touch membrane type keys that provides a convenient interface for entering the data.

Independent stirrer and platform keys on the front panel allow the user to easily start/stop stirrer movement or displacement of platform in the required direction at any time.

The instrument has the storage facility for 200 samples.

The samples being analyzed are automatically stored in the memory in different batch and sample numbers.

The system has three programming modes i.e. Routine, Sustain and Control mode.

It has the facility for setting up 20 different test methods using Routine and Sustain modes which are retained in the memory even when the power is switched OFF.

Provision has also been made for attachment of any dot matrix printer with centronics interface so that any of the stored setups/results can be printed.

The unit is provided with dissolution vessel with cover, having necessary arrangement to hold temperature sensor and the same is placed in the sturdy, acrylic water bath.

The large spread out stainless steel heater ensures perfectly uniform heating.

The instrument has dual channel temperature system with sensors to monitor the test temperature of dissolution vessel as well as that of the water bath.

The motorized platform's (stirrer unit) up/down movement of the instrument improves the accessibility for sampling. Stirrer speed is accurately controlled and maintained at +1 rpm by microcontroller as per IP, USP specifications.

The elapsed time for the current ongoing test is retained in the instruments memory.

In case of power failure during the run mode, when the instrument is switched

On again, the user has the option to run the test from the point of the power failure.

Specifications:-

General	
Stations	
6 Stations	
Display	
20 x 4 Line Alphanumeric LCD display with Backlit	
Keyboard	
12 x 4 Membrane keys	
LED's	
6 LED's, 3 LED's for Test status like Run, Alarm, End and 2 LED's for Platform up/down status and one for	

heater ON/OFF status.

Run Mode
Routine Sustain and Control mode. Facility for 20 different test setups available in Routine and Sustain mode.

Printer
Provision for the attachment of dot-matrix printer with centronics parallel port interface available.

Stirrer

Speed
25-200 RPM, + 1 RPM

Resolution
0.5 RPM

Accuracy
± 0.1 RPM

Temperature

Range	0 to 50 oC
Accuracy	± 0.2 oC
Temp. Control	Micro Controller Based using PT100/Semiconductor Sensor
Sampling	
Reaction Vessel	Reaction Vessel stirrer pedals and baskets
Heater	Heater
Power	± 10%, 50 Hz. AC
Main Section	Reaction Vessel with Acrylic Tank and Rectangular Cover Plate and Water Bath Temperature Sensor (T1) External Temperature Sensor (T2) for Vessel

Reaction Vessel capacity 1000 ml

(8 Nos. in Model - 1918 and (6 + 1) Nos. in Model - 1916)

Round Acrylic Cover Plate with Hole and a large slit

(8 Nos. in Model - 1918 & 6 Nos. in Model - 1916)

S.S. Paddle, S.S Wire Mesh Basket

(8 Nos. in Model - 1918 & 6 Nos. in Model - 1916)

Glass pipettes with rubber bellows

Mains Lead

Instruction Manual

Dust Cover

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003