

Product Name :
Thermal Cycler

Product Code :
NLAB-EDUSCHOOLEQ45025



Description :

Thermal Cycler

Technical Specification :

Thermal Cycler provides consistent, reliable results for laboratories with medium to high throughput.

From its large, touch-screen user interface to its unique, multi-format block, this cycle is loaded with features.

A large, full color touch screen serves as the operations center where all functions are accessed.

In addition, icons for favorite programs can be added for faster access.

The program wizard guides users through quickly setting up a protocol in a single screen.

Once entered, programs are shown graphically and can be edited by simply touching the step that requires modification.

Time and temperature increments can be built into programs as well as slower ramp rates.

Storage capabilities are unlimited; programs can be stored in public folders, private (password protected) folders or on a flash drive.

The full virtual keyboard allows for alphanumeric naming of programs and folders.

An in-situ adapter is available for use with slides.

Additionally, the unit may be purchased with a 384 well sample block.

The program wizard and 10 preinstalled programs make it easier than ever to get up and running.

From the "Home" screen, simply touch an icon to view the last run program, enter the program library, or use the program wizard to quickly enter a protocol.

The fully adjustable heated lid prevents condensation and evaporation of samples.

Lid temperature can be programmed, and when the block temperature is below 35°, the lid automatically shuts off.

Heating and cooling of the block are precisely and accurately controlled within exceptionally tight tolerances by a proprietary algorithm that simulates sample temperature.

With the multi-format block, there is no need for the expense of multiple interchangeable blocks.

The flexibility to accept 96 x 0.2ml tubes, a 96 well plate or 39 x 0.5ml tubes all in the same sample block.

Block (2ml tubes) / strips or 1 PCR plate or 39 x 0.5ml	
384 384 well plate	
In-situ Adapter:	
Temperature Control Range:	
Sample or block	

Accuracy/Uniformity:	
Temp. Rate (maximum)	
Bat Temp. 12°C, user adjustable	
Printer Method	
Yes, built-in/External temperature	
Multi user password protection	
Power Failure Restart:	
Power Supply to 275V, 50 to 60Hz	
Communication RS232	

Dimensions 9.9 in. / 26 x 36 x 25cm	
Weight/ 7.3kg	

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg,Ambala Cantt,Haryana,India. **Phone:** +91-9896600003